

2400W with PFC and Parallel Function



UL / CUL / TUV / CB / CE pending



- AC input 180~264V only
- Built-in active PFC function, PF>0.95
- Protections: Short circuit / Overload / Over voltage / Over temp. / Fan Alarm
- Forced air cooling by built-in DC with fan speed control function
- Output voltage can be trimmed between 20~110% of the rated output voltage
- High power density 12.5W/inch³
- Current sharing up to 2 units
- Alarm signal output (TTL signal & relay contact)
- Built-in 12V/0.1A auxiliary output for remote control
- Built-in remote ON-OFF control
- Built-in remote sense function
- 3 years warranty

AC input voltage range 180~264VAC; 254~370VDC
 DC adjustment range ±10% rated output voltage
 Overload protection 100%~110% constant current limiting, shut off after 5 sec., re-power on to recover (can adjust to continuous constant current limiting)
 Over voltage protection 115%~140% rated output voltage
 Setup, rise, hold up time 1000ms, 80ms, 10ms at full load and 230VAC
 Withstand voltage I/P-O/P:3kVAC, I/P-FG:1.5kVAC, 1 minute
 Working temperature -20~70°C (refer to output derating curve)
 Safety standards UL60950-1, TUV EN60950-1 pending
 EMC standards EN55022 class B, EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11, ENV50204
 Packing 3.8kg ; 4pcs / 16.2kg / 1.89CUFT

Stock No.	Model No.	Output	Tol.	R&N	Effi.
11741	RSP-2400-12	12V, 0~166.7A	±1%	150mV	86%
11742	RSP-2400-24	24V, 0~100A	±1%	150mV	89%
11743	RSP-2400-48	48V, 0~50A	±1%	200mV	90%